

CLLED Tapelight Series

Standard Output, High Output, and
Super High Output Accessories

Date: _____ Type: _____

Client: _____

Project: _____

Plug-In Power Supplies and Accessories



Plug-and-Play Power Supply
120V/12VAC. Includes AC wall plug and female power output plug for easy installation
CLLEDDRIVER24/12



Plug-and-Play 2-Way Splitter
Includes (1) male and (2) female connectors. Approximately 2' long.
CLLEDYCONN



Plug-and-Play 3-Way Splitter
Includes (1) male plug connector and (3) female plug connectors. Approximately 2' long.
CLLEDY3CONN



Plug-and-Play Power Supply
120V/12VAC. Includes AC wall plug and female power output plug for easy installation
CLLEDDRIVER36/12
CLLEDDRIVER60/12



Input Power Connector
Includes (1) male plug connector and (1) male flex tape connector.
CLLEDPC12
CLLEDPC19



Plug-and-Play Power Supply Extension
Includes male and female plug connectors.
CLLED48DRIVEXT
CLLED96DRIEXT



Output Power Connector
Includes (1) male plug connector and (1) female flex tape connector
CLLEDPT

Hardwire Power Supplies and Accessories



Hardwire Power Supply
120V/12VAC. Includes wire pigtailed on input and output sides. Must be maintained within an enclosure that meets local building codes and NEC (supplied by others).
CLLEDDRIVER20/12
CLLEDDRIVER60/12
CLLEDDRIVER60/12/277



Input Power Connector
Includes wire pigtail end and (1) male flex tap connector.
CLLEDPC12HW
CLLEDPC19HW



Hardwire Class II Enclosed Driver
120VAC/12VDC. Dimmable Class 2 driver. Compact self-enclosed driver with two (2) knockouts. Auto reset and short circuit protection. 120V Dimming only, no low voltage dimming.
CLLEDDRIVER20DIM - 120V/20W;
6-3/4"L x 2-58"W x 1-1/4"D
CLLEDDRIVER60DIM - 120V/60W;
6-3/4"L x 2-5/8"W x 1-1/4"D



Output Power Connector
Includes wire pigtail end and (1) female flex tape connector
CLLEDPCOUT



Female Connector
6" Connector includes wire pigtail end and (1) female plug connector. Used to add plug and play female connector to hardwire power supplies.
CLLEDFEMALEPC



Male Connector
6" Connector includes wire pigtail end and (1) male plug connector. Used for easy plug in connection to plug and play power supply; wire end can be connected to controllers at the screw terminals
CLLEDMALEPC


Linear Connectors



Bridge Connector
Blank section used to bridge a gap where LEDs are not necessary.
CLLED6CONN - 6"
CLLED12CONN - 12"



Cross Connector
Used to connect up to four (4) TLT segments. May be cut to create 2-way "L" connection or 3-way "T" connection.
CLLEDCONN



Short Female-to-Female Connector
Used to connect male to female connectors.
CLLEDFCONN



Display Supply & Lighting, Inc.

Display Supply & Lighting, Inc.
1247 Norwood Avenue
Itasca, IL 60143 USA
TF 800.468.1488
P 630.285.9660
F 630.285.9670
www.dslgroup.com

Copyright © 2016 Display Supply & Lighting, Inc. All rights reserved. All brand or product names are trademarks or registered trademarks of their respective owners. Due to continuous improvements and innovations, specifications may change without notice.

CLLED Tapelight Series

Standard Output, High Output, and
Super High Output Accessories

Date: _____ Type: _____

Client: _____

Project: _____

Controllers / Accessories



LED Power Repeater

Enables synchronized control of multiple runs from one controller.

CLLEDPowerREP



0-10V Dimming Module

for use with standard 0-10V dimmers. 4-3/4" L x 1-1/2" W x 1-1/2" D.

CLLEDDIMSA



DMX 512 CV Decoder

Designed to convert universal DMX 512 signal to PWM signal when used with a DMX 512 console. Can control single color or RGB LEDs.

6-3/16" L x 3-1/8" W x 1-5/8" D.

CLLEDDMXINTEF



Wall Plate Dimmer

allows adjustment of the brightness of the LEDs using the knob adjustment or the IR remote control.

3-7/16" square x 2-1/4" deep.

CLLEDDIMWP



Switch, LED Tapelight IR Cabinet

Allows on/off switching functionality for use with cabinet doors. 36W MAX. 1-1/2"L x 1-3/16"W x 5/16"H.

CLLEDTLPICB



Dimmer, LED Tapelight Touch

Allows adjustment of the brightness of the LEDs by touching the controller housing. 36W MAX. Not compatible with RGB tapelight.

1-1/2"L x 1-3/16"W x 5/16"H.

CLLEDTouchDIM



Switch, LED Tapelight IR Wireless Waving

Allows on/off switching functionality by waving an object within the IR Field. 36W MAX.

1-1/2"L x 1-3/16"W x 5/16"H.

CLLEDTLPiWV



Display Supply & Lighting, Inc.

Display Supply & Lighting, Inc.
1247 Norwood Avenue
Itasca, IL 60143 USA
TF 800.468.1488
P 630.285.9660
F 630.285.9670
www.dslgroup.com

Copyright © 2016 Display Supply & Lighting, Inc. All rights reserved. All brand or product names are trademarks or registered trademarks of their respective owners. Due to continuous improvements and innovations, specifications may change without notice.